



7 (& + 1 , & \$ / % 8 // (7 , 1



• • • • •

• • • • •

€ , f „

... € , † „

... † „

‡ ^

‰

• Š

<

...

‰ • ' f ' „

‡

• OE Ž •

‰ • ' ' ' ' •

• • • • •

•

•

•

•

•

• •





Figure 189 Straight Eye Socket

Size Range: 3/4" through 4"

Material: Galvanized steel

Service: Structural attachment to connect threaded rod to structure.

Approvals: FM and cULus listed.

Installation:

- Thread rod completely into hanger. Secure rod by tightening jam nut against bottom of hanger.
- Secure hanger to structural member with recommended fasteners.

Features:

- Pre-formed threads for easy rod assembly.

Ordering: Specify figure number and description.

Description	Pipe Sizes	Rod Size	Max. Load
Straight Eye Socket Hanger	3/4" - 4"	3/8-16 UNC	250 lbs.

FASTENERS		
Description	Quantity	Pipe Size
#14 x 2" Wood Screw	2	*3/4" - 2"
1/2" x 3" Lag Screw	*1	3/4" - 4"
3/8-16 UNC Jam Nut	1	3/4" - 4"

* Lag screw not required for 3/4" - 2" pipe sizes using the alternate option of (2) wood screws.



For Listings/Approval Details and Limitations visit www.anvilintl.com or contact an Anvil®/AnvilStar™ Sales Rep.

FIG. 189: DIMENSIONS (IN)	
A	B
2.28	1.10

Notes:

1. For fire protection installation follow the requirements of National Fire Protection Association, NFPA-13 and local codes.
2. To assure proper performance, installer is responsible for:
 - a. Structural integrity of attachment member to safely handle load requirements.
 - b. Securely tightening jam nut on the hanger rod.



Figure 190 Off-Set Eye Socket

Size Range: 3/4" through 4"

Material: Galvanized steel

Service: Structural attachment to connect threaded rod to structure.

Approvals: FM and cULus listed.

Installation:

- Thread rod completely into hanger. Secure rod by tightening jam nut against bottom of hanger.
- Secure hanger to structural member with recommended fasteners.

Features:

- Pre-formed threads for easy rod assembly.
- Off-set angle provides unlimited vertical adjustment.

Ordering: Specify figure number and description.

Description	Pipe Sizes	Rod Size	Max. Load
Off-Set Eye Socket Hanger	3/4" - 4"	3/8-16 UNC	250 lbs.

FASTENERS		
Description	Quantity	Pipe Size
#14 x 2" Wood Screw	2	*3/4" - 2"
1/2" x 3" Lag Screw	*1	3/4" - 4"
3/8-16 UNC Jam Nut	1	3/4" - 4"

* Lag screw not required for 3/4" - 2" pipe sizes using the alternate option of (2) wood screws.



For Listings/Approval Details and Limitations visit www.anvilintl.com or contact an Anvil®/AnvilStar™ Sales Rep.

FIG. 190: DIMENSIONS (IN)	
A	B
3.38	1.10

Notes:

1. For fire protection installation follow the requirements of National Fire Protection Association, NFPA-13 and local codes.
2. To assure proper performance, installer is responsible for:
 - a. Structural integrity of attachment member to safely handle load requirements.
 - b. Securely tightening jam nut on the hanger rod.